

Product Specifications

FlashCheck Ruggedized Screw Tip Digital Thermometer

Measurement Range	-58°F to 572°F (-50°C to 300°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±0.9°F (±0.5°C) from 14°F to 212°F (-10°C to 100°C) ±4.5°F (±2.5°C) from 392°F to 572°F (200°C to 300°C) or ±2.7°F (1.5°C)
Response Time	8 seconds between 77°F to 212°F (25°C to 100°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	1 second
Display Size	0.98 in W x 0.59 in H (25mm W x 15mm H)
Calibration	Automatic Calibration button
Battery	3V CR2032
Battery Life	About 5,700 hours in continuous operation
Body Casing	ABS Plastic
Probe Length	3.9 in (99mm)
Probe Diameter	4.72 in x 0.19 in (120mm x 5) screw tip 1.8 in x 0.23 in (30mm x 6mm)
Waterproof Rating	IP67
Factory Calibration	CE, NSF, NIST traceable calibration
Compliance Certificate	Manufacturer's Certificate of Compliance, NIST traceable, NSF, CE, ROHS



Model 11055

- Screw tip penetrates frozen foods
- Automatic calibration feature
- IP67 waterproof, sanitizable, dirt and grease resistant
- Maximum & minimum reading memory
- Data hold function
- °F/°C selectable

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system



SS 11055 19H1

