

Product Specifications

FlashLink CT -80°C In-Transit Logger

Measurement Range	-80°C to 47°C (-112°F to 117°F)
Temperature Accuracy	0.5°C (±1.0°F) From -60°C to 30°C (-76°F to 86°F) 1°C (±2°F) From -80°C to -60°C (-112°F to -76°F) 2°C (±3°F) From 30°C to 47°C (86°F to 117°F)
Temperature Resolution	0.1°C/F
Data Capacity	3,824 Data points
Data Download Time	5 seconds
Factory Programmable Alarm Levels	High & low limits over entire range
LED Indicators	Flashing red for alarm, green for active
Battery	Single AA Lithium Battery
Dimensions	4.03" x 1.75" x 1.18" (102.55 mm x 44.5 mm x 30 mm)
Weight	2.82 oz. (80 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
IP Rating	68 (with cap on)
Certification	CE Mark, NIST traceable calibration, RoHS Compliant, BSS 7061 Compliant
System Requirements	Windows PC with current operating system, Adobe Reader, FlashPDF software
Download Requirements	8-Pin to USB Adapter



Models

5-Day	15-Day	45-Day	75-Day
20762	20763	20764	20769

- Compact, single-use, in-transit data logger
- Patented Shadow Log™ feature guarantees data even if the operator forgets to start the device
- FlashPDF software (21 CFR Part 11 Compliant)
- Download data to PC with 8-Pin to USB Adapter or print with CT Graphics Printer
- Ideal for dry ice shipments

Patent No. 6,088, 514

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0074_16C4

