

# Product Specifications

## Jumbo Display Wall Mount Thermo-Hygrometer

<b>Temperature Range</b>	Internal: 32°F to 122°F (0°C to 50°C) External Probe: -58°F to 158°F (-50°C to 70°C)
<b>Humidity Range</b>	Internal: 20% to 90%
<b>Temperature Accuracy(Int. &amp; Ext.)</b>	±1.8°F (1°C) from -40°F to 158°F (-40°C to 70°C)
<b>Humidity Accuracy(Internal)</b>	±5% R.H. from 35% to 85% R.H. at 77°F (25°C)
<b>External Temperature Sensor</b>	Cable length: 10 ft/3meters; probe: 30mm (L) x 5mm (dia.) tip
<b>Resolution</b>	R.H.1%, temperature 0.1°F /0.1°C
<b>Display Reading Update</b>	10 Seconds
<b>Display Window Size</b>	3.11 in. (W) x 2.79 in. (H) (79 mm x 66 mm)
<b>Character Height within Display</b>	1.06 in. (17mm)
<b>Product Size</b>	3.85 in. (W) x 4.33 in. (H) x .82 in. (D) (98 mm x 110 mm x 21 mm)
<b>Weight</b>	2.4 oz. (68 g)
<b>Body Casing</b>	Polycarbonate and ABS plastic
<b>Sensor Type</b>	Temperature: thermistor Humidity: electronic capacitance polymer film
<b>Battery</b>	AAA (quantity 2 each)
<b>Freeze Alarm Setting</b>	If set, alarm will sound when external temperature is ≤ 32°F (0°C)
<b>Waterproof Rating</b>	IP67 (Probe Only)
<b>Certification/ Calibration</b>	CE mark/ N.I.S.T. traceable



### Model 13307

- Internal temperature and humidity sensors
- External temperature probe
- Freeze alert
- °C/°F selectable
- Jumbo display for temperature and humidity
- Min/Max memory - lowest and highest readings stored for instant recall
- Low Battery Indication

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 13307 16J1

