

Product Specifications

FlashLink 2.4 GHz Wireless Receiver

Operating Temperature Range	-4°F to +122°F (-20°C to +50°C)
Frequency Range	2.405 to 2.475 GHz, IEEE 802.15.4 PHY compliant
Transmit	+13.0 dBm (including 2.2 dBi gain of the antenna)
Receive	-103.0 dBm
Typical Range	indoor: 164 feet (50m), outdoor: 328 feet (100m)
Battery Backup Life	5 days
Interface	RS232
Backup Battery	3 rechargeable AA nickel metal hybrid
Antenna	External omni-directional swivel antenna, SMA connector
Waterproof Rating	IP20
Mount	4 hole screw mount
Weight	8.2 oz (232 g)
Color	White
Dimension	2.0 x 2.7 x 3.9 inch (50.0 x 68.0 x 100.0 mm)
Power Source	External, 6.0 – 12.6 V, 500 mA
Certification	CE mark, RoHS
Programming & Downloading	FlashRF Manager Software (order PN 20169)



Model 20170

- Network control module, enables all communication between RFID components and back office system
- Mesh networking technology optimizes data transfer
- Self configuring and fault-tolerant to ensure quality communication (Real Time Location System)
- Easily reprogrammable for firmware updates
- Internal back-up power source

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 20170 17D1

