

# Product Specifications

## FlashLink. USB Reusable Data Logger

<b>Measurement Range</b>	-40°F to 122°F (-40°C to 50°C)
<b>Temperature Resolution</b>	0.1°F/°C
<b>Accuracy</b>	±1.0°F from 14°F to 77°F (±0.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
<b>Data Capacity</b>	3823 points
<b>Data Download Time</b>	2 seconds typical for 3823 points
<b>Programmable Alarm Levels</b>	High & Low levels over entire range, displayed on LCD
<b>Battery</b>	Coin cell lithium battery
<b>Dimensions/Body</b>	1.575 in x 3.189 in x .575 in (40 mm x 81 mm x 13 mm)
<b>Casing</b>	PC/ABS plastic
<b>Weight</b>	1.3 oz. (36 grams)
<b>Shock Resistance</b>	Withstands 3-foot (1 meter) drop to hard surface
<b>Certification</b>	CE Mark, NIST traceable, RoHS Compliant
<b>Display</b>	LCD, Red LED Alarm
<b>Waterproof Rating</b>	IP64 with silicon cap on
<b>Storage conditions</b>	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
<b>System Requirements</b>	Windows PC with current operating system Adobe Reader
<b>Programming</b>	FlashPDF Program Manager software
<b>Download Requirements</b>	Direct USB connection



### Model 20908

- Single channel, internal sensor for ambient air temperature
- User programmable: manual or automatic start, sample interval, alarm limits, data tags
- Large, easy to read LCD display
- Trip history statistics available on LCD
- NIST traceable and CE Mark
- USB Connection

Patent No. 6,088,514



DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 20908 1611

