

# Product Specifications

## FlashLink PDF Multi-Use Data Logger

<b>Measurement Range</b>	-40°F to 122°F (-40°C to 50°C)
<b>Temperature Resolution</b>	0.2°F /0.1°C
<b>Accuracy</b>	±1.0°F from -4°F to 113°F; (±0.5°C from -20°C to 45°C) ±2.0°F above 113°F; (±1.0°C above 45°C) ±2.0°F below -4°F; (±1.0°C below -20°C)
<b>Data Capacity</b>	16,112 points
<b>Sample Interval</b>	5 minutes
<b>Data Download Time</b>	30 seconds typical
<b>Factory Programmable Alarm Limits</b>	High/low limits over entire temp range
<b>Battery</b>	Coin Cell Lithium battery
<b>Dimensions</b>	1.93" x 3.62" x 0.67" (49mm x 92mm x 17mm)
<b>Casing</b>	ABS plastic
<b>Weight</b>	1.6 oz. (45.36 grams)
<b>Shock Resistance</b>	Withstands 3-foot (1 meter) drop to hard surface
<b>Certification</b>	CE Mark, Calibration traceable to NIST, ROHS Compliant, BSS 7061 Compliant
<b>Display</b>	LCD, Red LED Alarm
<b>Storage Conditions</b>	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
<b>PDF Standards</b>	Complies with ISO19005-1, PDF/A, 21 CFR Part 11
<b>System Requirements</b>	PC with current operating system Adobe Reader
<b>Download Requirements</b>	Direct USB connection



Models	
°F	40202
°C	40203

- Unit is designed to be used multiple times
- Data logger is factory pre-programmed
- No software needed to download data
- Built-in USB connector, no special reading devices required
- Stops recording after downloading data
- Automatically creates secure PDF report and CSV file
- Push-button resets and restarts unit for next use
- Temperature statistics available on LCD
- Custom configuring available for logging parameters, alarms, and delayed start

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 40202-X\_17C2

