

# Product Specifications

## FlashCheck Lollipop Min/Max Thermometer

<b>Measurement Range</b>	-40°F to 311°F (-40°C to 155°C)
<b>Operating Range</b>	32°F to 122°F (0°C to 50°C)
<b>Accuracy</b>	±2°F (-40°F to -4°F); ±1°C (-40°C to -20°C) ±1°F(-4°F to 131°F); ±0.5°C (-20°C to 55°C) ±2°F (131°F to 311°F); ±1°C (55°C to 155°C) or ±1%, whichever is greatest
<b>Sensor</b>	Thermistor
<b>Display Resolution</b>	0.1°F /°C
<b>Display Reading Update</b>	1 second
<b>Display Window Size</b>	0.77 in W x 0.37 in H (19.5 mm W x 9.5 mm H)
<b>Calibration</b>	Factory calibrated to NIST traceable standards
<b>Battery</b>	Button Cell Alkaline
<b>Body Casing</b>	ABS plastic
<b>Probe Dimensions</b>	4.13" L x 0.14" Dia, Reduced tip 0.1" Dia (105 mm L x 3.56 mm Dia, Reduced tip 2.5 mm Dia)
<b>Weight</b>	1.25 oz. (35.4 gm)
<b>Waterproof Rating</b>	IP65
<b>Certification</b>	CE, RoHS, NIST traceable, manufacturers certificate of compliance available



### Model 11040

- °F/°C selectable
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof
- Reduced Tip Probe
- Complies with FDA Food Code 4-203.11

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0183 15G1

