

# Product Specifications

## FlashLink. NOW 4G Real-Time In-Transit Logger

<b>Temperature Range</b>	-30°C to 60°C (-22°F to 140°F)
<b>Temperature Accuracy</b>	±0.5°C from -20°C to 40°C (±0.9°F from -4°F to 104°F) ±1.0°C (2.0°F) Other
<b>Temperature Resolution</b>	0.1°C/°F
<b>Temperature Sensor Type</b>	Internal Digital Temperature Sensor (NIST traceable)
<b>Temperature Scale</b>	Dual-scale °F/°C (Default °C)
<b>Humidity Range</b>	5% to 95% RH
<b>Humidity Accuracy</b>	±3% from 20% to 80%RH ±5% for other
<b>Light Detector</b>	0-20 Lx
<b>Shock Sensor</b>	0-8G (Factory configurable options up to 16G)
<b>Usage Type</b>	Single Use
<b>Data Capacity</b>	Max 27000 readings
<b>Logging Interval</b>	10 Min.
<b>Data Upload Interval</b>	90 Min.
<b>Trip Duration</b>	70 Days
<b>Communication</b>	Global LTE Cat-1 4G/5G network, with 2G Fallback
<b>SIM</b>	Internal Embedded (Global Data Roaming) Nano Sim
<b>Power Source</b>	Non-Lithium Ni-MH
<b>Battery Shelf Life</b>	1 Year
<b>Logger Dimensions</b>	4.2in [with loop: 4.5in] x 2.7in x 0.9in (106.4mm [with loop: 113.8mm] x 68.6mm x 22.3mm)
<b>Waterproof Rating</b>	IP54
<b>Certification</b>	FCC, CE, ROHS, NIST traceable temperature accuracy
<b>PDF Report Backup</b>	USB-C to USB cable to download full trip PDF report



### Model 23002

- Equipped with global network compatibility, Location Based Services (LBS), and precision accuracy through Wi-Fi triangulation positioning for reliable real-time monitoring
- Monitors in-transit real-time location, temperature, humidity, shock, and light exposure
- Our Cloud Service platforms offer different levels of access to optimize user experience and API integration into customer systems
- Easily toggle between °F and °C on the LCD display upon activation
- Customizable trip durations for 12, 30, 70, 90, 120 days

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 23002\_25D3

