

Product Specifications

FlashLink[®] NOW 4G Real-Time In-Transit Logger

Temperature Range	-30°C to 60°C (-22°F to 140°F)
Temperature Accuracy	±0.5°C from -20°C to 40°C (±0.9°F from -4°F to 104°F) ±1.0°C (2.0°F) Other
Temperature Resolution	0.1°C/°F
Temperature Sensor Type	Internal Digital Temperature Sensor (NIST traceable)
Temperature Scale	Dual-scale °F/°C (Default °C)
Humidity Range	5% to 95% RH
Humidity Accuracy	±3% from 20% to 80%RH ±5% for other
Light Detector	On / Off, triggers at 15 Lux
Shock Sensor	4g, height 5cm to 10cm (Factory Customizable options up to 16g)
Usage Type	Single Use
Data Capacity	Max 27000 readings
Logging Interval	10 Min.
Data Upload Interval	90 Min.
Trip Duration	70 Days
Communication	Global LTE Cat-1 4G/5G network, with 2G Fallback
SIM	Internal Embedded (Global Data Roaming) Nano Sim
Power Source	Non-Lithium Ni-MH
Battery Shelf Life	1 Year
Logger Dimensions	4.2in [with loop: 4.5in] x 2.7in x 0.9in (106.4mm [with loop: 113.8mm] x 68.6mm x 22.3mm)
Waterproof Rating	IP54
Certification	FCC, CE, ROHS, NIST traceable temperature accuracy
PDF Report Backup	USB-C to USB cable to download full trip PDF report



Model 23002

- Equipped with global network compatibility, Location Based Services (LBS), and precision accuracy through Wi-Fi triangulation positioning for reliable real-time monitoring
- Monitors in-transit real-time location, temperature, humidity, shock, and light exposure
- Our Cloud Service platforms offer different levels of access to optimize user experience and API integration into customer systems
- Easily toggle between °F and °C on the LCD display upon activation
- Customizable trip durations for 12, 30, 70, 90, 120 days

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 23002_25D1

