

Product Specifications

FlashLink® NOW 4G/5G Real Time In-Transit BLE Gateway

Temperature Range	-30°C to 70°C (-22°F to 158°F)
Temperature Accuracy	±0.5°C from -10°C to 45°C (±0.9°F from 14°F to 113°F), ±1.0°C (2.0°F) Other
Temperature Resolution	0.1°C/F
Sensor Type	Internal Digital Temperature and Humidity Sensor
Humidity Measurement Range	5% to 95%RH
Humidity Accuracy	±3% from 20% to 80%RH ±5% for other
Light Sensor Range	0 to 52000 lux
Shock Sensor	0-8g height: 5-10cm
Usage Type	Single-use
Data Capacity	Max 28800 Readings
Logging Interval	20 Min.
Data Upload Interval	90 Min.
Trip Duration	70-Day (based on logging and uploading intervals)
Communication	Global 4G/5G network
SIM	Internal Embedded (Global Data Roaming)
BLE Protocol	5.2
BLE Connection	Up to 5 BLE Loggers
Power Source	Lithium Battery
Battery Shelf Life	1 year
Logger Dimensions	4.05in x 2.41in x 1.18in (103mm x 61.3mm x 30mm)
Weight	4.16 oz (118 grams)
Waterproof Rating	IP64
Certification	FCC, RoHS, NIST traceable temperature accuracy
PDF Report Backup	Micro USB to USB cable to download full trip PDF report



Model 22391

- Equipped with global network communication compatibility and precision location accuracy through Wi-Fi triangulation positioning
- Monitors and provides alerts for in-transit real-time location, temperature, humidity, shock, and light
- A unified cloud platform connecting cold chain IoT devices and applications, with seamless integration, automation, built-in analytics and business intelligence.
- USB option to download PDF trip data should GSM Network not be available

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS_22391_25H1

 **DeltaTrak**