

Product Specifications

FlashLink® Mini PDF In-Transit Logger

Measurement Range	-40°F to 140°F (-40°C TO 60°C)
Temperature Accuracy	±1.0°F from -4°F to 14°F (±0.5°C from -20°C to -10°C) ±0.6°F from 14°F to 50°F (±0.3°C from -10°C to 10°C) ±1.0°F from 50°F to 77°F (±0.5°C from 10°C to 25°C) ±1.8°F if < -4°F or > 77°F (±1.0°C if < -20°C or > 25°C)
Data Capacity	12,288 Data Points
Temperature Scale	°F/°C
Data Download Time	5 seconds typical
Logging Interval	10 Minutes
Trip Duration	85 days
Low/High Alarms Settings	Low Alarm: 45.0°F / 7.2°C
Factory Programmable	High & Low levels over entire range
Delay Start	30 minutes
Battery	Coin Cell Battery
Dimensions	1.858in x 3.071 in x 0.402 in (47.2mm x 78mm x 10.2mm)
Weight	0.854 oz. (24.2 grams)
Certification	RTCA/DO-160G Sect 21.5, CE Mark, Calibration traceable to NIST, RoHS Compliant
Display	Green and Red LED
Waterproof Rating	IP54 with silicone cap
Shelf Life	18 Months
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system, Adobe Reader
Download Requirements	Direct USB connection to PC, tablet or printer



Model 31010-25

- Compact, single-use temperature logger
- Shadow Log® guarantees trip data
- One model for any trip duration, up to 85 days
- No software required to download reports
- Built-in USB connector, no special reading device
- PDF and CSV reports in both °F and °C scales
- Recorded data automatically scales to fit full graph
- Save and share files from PC or tablet

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 31010-25 24E3

 **DeltaTrak**®