

# Product Specifications

## FlashLink<sup>®</sup> NOW 4G Real-Time In-Transit Logger

<b>Temperature Range</b>	-30°C to 55°C (-22°F to 131°F)
<b>Temperature Accuracy</b>	±0.5°C from -10°C to 40°C (±0.9°F from 14°F to 104°F) ±1.0°C (°2.0°F) Other
<b>Temperature Resolution</b>	0.1°C/°F
<b>Sensor Type</b>	Internal Digital Temperature Sensor
<b>Light Detector</b>	0-20Lx
<b>Temperature Scale</b>	Dual-scale °F/°C (Default °F)
<b>Usage Type</b>	Single Use
<b>Data Capacity</b>	Max 27000 readings
<b>Logging Interval</b>	5 Min.
<b>Data Upload Interval</b>	20 Min.
<b>Trip Duration</b>	Up to 20 Days at -5°C to 55°C (23°F to 131°F) Up to 15 Days at -10°C to 55°C (14°F to 131°F) Up to 12 Days at -25°C to 55°C (-13°F to 131°F)
<b>Communication</b>	Global 4G/5G network, with 2G Fallback
<b>SIM</b>	Internal Embedded Nano Sim (Global Data Roaming)
<b>Power Source</b>	Non-Lithium Battery [Alkaline]
<b>Battery Shelf Life</b>	12 Months
<b>Logger Dimensions</b>	4.2in [with loop: 4.5in] x 2.7in x 0.9in (106.4mm [with loop: 113.8mm] x 68.6mm x 22.3mm)
<b>Weight</b>	6.14 oz (174 grams)
<b>Waterproof Rating</b>	IP66
<b>Certification</b>	FCC, CE, ROHS, TELEC, NIST, WEEE, ISO17025(optional)
<b>PDF Report Backup</b>	Download full trip PDF report via USB-C



### Model 23006

- Equipped with global network communication compatibility and precision location accuracy through Wi-Fi triangulation positioning
- Monitors and provides alerts for in-transit real-time location, temperature, and light
- A unified cloud platform connecting cold chain IoT devices and applications, with seamless integration, automation, built-in analytics and business intelligence.
- Easily switch between °F and °C on the LCD display upon activation

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 23006\_26D1

