FlashLink® NOW 4G/5G Real Time In-Transit BLE Gateway

Temperature Range	-30°C to 70°C (-22°F to 158°F)
Temperature Accuracy	±0.5°C from -10°C to 45°C (±0.9°F from 14°F to 113°F), ±1.0°C (2.0°F) Other
Temperature Resolution	0.1°C/°F
Sensor Type	Internal Digital Temperature and Humidity Sensor
Humidity Measurement Range	5% to 95%RH
Humidity Accuracy	±3% from 20% to 80%RH ±5% for other
Light Sensor Range	0 to 52000 lux
Shock Sensor	0-8g height: 5-10cm
Usage Type	Single-use
Data Capacity	Max 28800 Readings
Logging Interval	20 Min.
Data Upload Interval	90 Min.
Trip Duration	70-Day (based on logging and uploading intervals)
Communication	Global 4G/5G network
SIM	Internal Embedded (Global Data Roaming)
BLE Protocol	5.2
BLE Connection	Up to 5 BLE Loggers
Power Source	Lithium Battery
Battery Shelf Life	1 year
Logger Dimensions	4.05in x 2.41in x 1.18in (103mm x 61.3mm x 30mm)
Weight	4.16 oz (118 grams)
Waterproof Rating	IP64
Certification	FCC, RoHS, NIST traceable temperature accuracy
PDF Report Backup	Micro USB to USB cable to download full trip PDF report



Item #: 13010204 Model: 22391

- Equipped with global network communication compatibility and precision location accuracy through Wi-Fi triangulation positioning
- Monitors and provides alerts for in-transit real-time location, temperature, humidity, shock, and light
- A unified cloud platform connecting cold chain IoT devices and applications, with seamless integration, automation, built-in analytics and business intelligence.
- USB option to download PDF trip data should GSM Network not be available

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS_22391_25H1

DeltaTrak®